

kreon rokko

kreon rokko is a black or white semi-recessed IP 65 luminaire that produces a soft gradient light and is ideal for pathway and orientation lighting. Whether used indoors or outdoors kreon rokko can create a formal continuity in architecture from the interior to the exterior of high end residential or hospitality projects.



kreon mini rokko and kreon mini square rokko can be installed in brickwork or cavity walls and require a minimum depth. These luminaires are offered with a 2700K, CRI80+ LED, driver included.









mini rokko, black



mini square rokko, white




	Colour	KR-code	Light sources	Optional accessories
 mini rokko ⌀ LxW 125x75 D 80 Gear: excl. 	<input type="radio"/>	KR943021	①	<input type="checkbox"/>
	<input checked="" type="radio"/>	KR943022	①	<input type="checkbox"/>
 mini rokko ⌀ LxW 125x75 D 80 Gear: incl. 	<input type="radio"/>	KR943121	②	<input type="checkbox"/>
	<input checked="" type="radio"/>	KR943122	②	<input type="checkbox"/>
 mini square rokko ⌀ LxW 125x125 D 85 Gear: incl. 	<input type="radio"/>	KR943321	③	<input type="checkbox"/>
	<input checked="" type="radio"/>	KR943322	③	<input type="checkbox"/>
Optional accessories				
Installation set	KR743002	Plasterboard installation set		
Concrete pouring mould	KR743004	Concrete pouring mould for mini rokko		
	KR743304	Concrete pouring mould for mini square rokko		
Driver	KR772034	LED driver, 700mA, ON/OFF, 20W		
	KR772232	LED driver, 700mA, 1-10V, 20W		
	KR772134	LED driver, 700mA, DALI, 20W		

	CRI	CCT	Voltage	Wattage	Drive current	Fixture lumen
① LED	CR180+	3000K		2,3W	700mA	72lm
② LED	CR180+	3000K	230V	2,3W		72lm
③ LED	CR180+	3000K	230V	6,9W		226lm

REMARKS
 ① 1 driver (6W) can power up to 2 fittings.

IP65

Installation set



Concrete pouring mould

