



# kreon up

kreon up is a range of IP67 rated luminaires characterised by its minimal appearance and optical functionality. The range is offered in three sizes in square, circular or linear forms, is finished with black or white backed toughened glass with a satin stainless steel trim. LED modules are deep-set within the luminaires and are controlled by a choice of anti-glare louvres for precise uplighting; brightness limiting diffuser for ambient or orientation lighting; wallwash optic for vertical luminance or wall grazing optic for highlighting and bringing out the wall structure. kreon up 40 is also available as a surface mounted fixed downlight or linear wall grazer.



up 40 circular, black, with baffle







up 80, black



up 165 circular, white

# kreon up 40



**up 40**  
 ☉ LxW 45x45 D 60 ①

**up 40 surface mounted**

**up 40 circular**  
 ☉ Ø 45 D 60

**up 40 circular surface mounted**

### ■ Optional accessories

Driver ②

Colour  
 KR-code  
 Light sources  
 9027 2700K, CRI90  
 9030 2700K, CRI90  
 SP Spot  
 FL Flood  
 SB Spot with baffle  
 FB Flood with baffle  
 XC (optional) For recessed wall or ceiling installation  
 Optional accessories


○	KR952111	①	●	●	●	●	●	●	●	●	■
●	KR952112	①	●	●	●	●	●	●	●	●	■
○	KR952011	①	●	●	●	●	●	●	●		■
●	KR952012	①	●	●	●	●	●	●	●		■
○	KR952611	①	●	●	●	●	●	●	●	●	■
●	KR952612	①	●	●	●	●	●	●	●	●	■
○	KR952911	①	●	●	●	●	●	●	●		■
●	KR952912	①	●	●	●	●	●	●	●		■
	KR772630										
	KR772752										
	KR772853										

### REMARKS


- ① Build-in dimensions of fixture with XC-option: LxW = 45x47
- ② Must be placed on remote.
- ③ Driver can be used for at least 4 fixtures.





Thickness boardmaterial:  
 9-18mm  
 Gear excluded.  
 ☉ IP67

XC



Baffle option





	Colour	KR-code	Light sources	8027 2700K, CRI80	9027 2700K, CRI90	Optional accessories
<b>up 80</b> ⌀ LxW 86x86 D 84 Diffusing lens incl.	○	<a href="#">KR952101</a>	①	●	●	■
	●	<a href="#">KR952102</a>	①	●	●	■
<b>up 80</b> ⌀ LxW 86x86 D 84 15° optic & anti glare louvre incl.	○	<a href="#">KR952121</a>	②	●	●	■
	●	<a href="#">KR952122</a>	②	●	●	■
<b>up 80 wallwasher</b> ⌀ LxW 86x86 D 84	○	<a href="#">KR952171</a>	③	●	●	■
	●	<a href="#">KR952172</a>	③	●	●	■
<b>up 80 circular</b> ⌀ ⌀ 86 D 84 Diffusing lens incl.	○	<a href="#">KR952601</a>	①	●	●	■
	●	<a href="#">KR952602</a>	①	●	●	■
<b>up 80 circular</b> ⌀ ⌀ 86 D 84, 15° optic & anti glare louvre incl.	○	<a href="#">KR952621</a>	②	●	●	■
	●	<a href="#">KR952622</a>	②	●	●	■
<b>up 80 circular wallwasher</b> ⌀ ⌀ 86 D 84	○	<a href="#">KR952671</a>	③	●	●	■
	●	<a href="#">KR952672</a>	③	●	●	■

■ **Optional accessories**

Matchbox	<a href="#">KR752103</a>	Matchbox up 80
	<a href="#">KR752603</a>	Matchbox up 80 circular
Driver ①	<a href="#">KR772830</a>	LED driver, 700 mA, ON/OFF, 35W (IP68)
	<a href="#">KR772752</a>	LED driver, 700 mA, 1-10V, 12W (IP67)
	<a href="#">KR772753</a>	LED driver, 700 mA, DALI, 70W (IP68)


	CRI	CCT	Wattage	Drive current	Fixture lumen
① LED	CRI80+	2700K	8,4W	700mA	272lm
	CRI90	2700K	8,4W	700mA	272lm
② LED	CRI80+	2700K	8,4W	700mA	458lm
	CRI90	2700K	8,4W	700mA	458lm
③ LED	CRI80+	2700K	8,4W	700mA	534lm
	CRI90	2700K	8,4W	700mA	534lm

**REMARKS**


① Must be placed on remote.

Thickness boardmaterial:  
6-35mm  
Gear excluded.  
⌀ IP67 - IK10




Matchbox up 80






Matchbox up 80 circular



# kreon up 80 glass series



	Colour	KR-code	Light sources	8027 2700K, CRI80	Optional accessories
 <b>up 80 circular stub</b> ⌀ 86 D 84	●	<a href="#">KR952702</a>	①	●	■
 <b>up 80 circular gherkin</b> ⌀ 86 D 84	●	<a href="#">KR952712</a>	①	●	■
 <b>up 80 circular freeform stub</b> ⌀ 86 D 84	●	<a href="#">KR952722</a>	①	●	■
<b>■ Optional accessories</b>					
Matchbox	<a href="#">KR752603</a>		Matchbox up 80 circular		
Driver ①	<a href="#">KR772830</a>		LED driver, 700 mA, ON/OFF, 12W (IP67)		
	<a href="#">KR772752</a>		LED driver, 700 mA, 1-10V, 35W (IP68)		
	<a href="#">KR772753</a>		LED driver, 700 mA, DALI, 70W (IP68)		


	CRI	CCT	Wattage	Drive current	Fixture lumen
① LED	CRI80+	2700K	8,4W	700mA	152lm

## REMARKS




① Must be placed on remote.

The stated dimensions are only to be used as a reference. Actual dimensions may vary. Each unit is unique due to the artisanal production technique. Gear excluded.  
 ⌀ IP67

Matchbox up 80 circular



# kreon up 165



**up 165**  
 ⌀ LxW 156x156 D 97  
 Gear: excl., anti-glare louvre incl.

**up 165 wallwasher**  
 ⌀ LxW 156x156 D 97  
 Gear: excl.

**up 165 circular**  
 ⌀ Ø156 D 97  
 Gear: excl., anti-glare louvre incl.

**up 165 circular wallwasher**  
 ⌀ Ø156 D 97  
 Gear: excl.

■ **Optional accessories**

Matchbox

<b>KR782103</b>	Matchbox for up 165
<b>KR782104</b>	Matchbox for gear for up 165 (for fixtures gear excl.)
<b>KR782603</b>	Matchbox for up 165 circular
<b>KR782604</b>	Matchbox for gear for up 165 circular (for fixtures gear excl.)

Coupling sleeve

<b>KR782105</b>	Coupling sleeve
-----------------	-----------------


Driver

<b>KR772630</b>	LED driver, 700 mA, ON/OFF, 30W (IP68)
<b>KR772852</b>	LED driver, 700 mA, 1-10V, 30W (IP67)
<b>KR772853</b>	LED driver, 700 mA, DALI, 30W (IP68)


	CRI	CCT	Wattage	Drive current	Fixture lumen
① LED	CR183	2700K	15,2W	700mA	824lm
	CR190	2700K	17,1W	700mA	824lm
② LED	CR183	2700K	15,2W	700mA	1099lm
	CR190	2700K	17,1W	700mA	1099lm

**REMARKS**  
 Thickness boardmaterial:  
 6-35mm  
 IP67 - IK10


Matchbox up 165




Matchbox up 165 circular



Matchbox up 165 for gear



Matchbox up 165 circular for gear



Colour	KR-code	Light sources	8327 2700K, CR183	9027 2700K, CR190	C5 Maritime	Optional accessories
○	<b>KR982121</b>	①	●	●	●	■
●	<b>KR982122</b>	①	●	●	●	■
○	<b>KR982181</b>	②	●	●	●	■
●	<b>KR982182</b>	②	●	●	●	■
○	<b>KR982621</b>	①	●	●	●	■
●	<b>KR982622</b>	①	●	●	●	■
○	<b>KR982681</b>	②	●	●	●	■
●	<b>KR982682</b>	②	●	●	●	■


# kreon up in-line

kreon up in-line is a range of floor recessed uplighters characterised by its minimal appearance and optical functionality. The range, offered in two sizes in both square and circular forms, is finished with black or white backed toughened glass. LED modules are deep-set within the luminaires and are controlled by a choice of anti-glare louvres for precise uplighting, brightness limiting diffusers for ambient or orientation lighting and wallwash optics for vertical luminance.


kreon up in-line benefits from a stainless steel trim that provides a seamless juncture to minimise integration. The units are sealed to IP67 and have a die cast aluminium and stainless steel housing to provide protection from the harshest environments. The maritime versions are specially pre-treated for maximum protection against corrosion in salty environments.




up in-line 80 wallwasher, white



up in-line 80 circular, black







up in-line 165, black



up in-line 165 circular, white

# kreon up in-line 80



	Colour	KR-code	Light sources	8027 2700K, CRI80	9027 2700K, CRI90	Optional accessories
<b>up in-line 80</b> ⌀ LxW 85x85 D 84 Diffusing lens incl.	○	<a href="#">KR952301</a>	①	●	●	■
	●	<a href="#">KR952302</a>	①	●	●	■
<b>up in-line 80</b> ⌀ LxW 85x85 D 84 15° optic & anti-glare louvre incl.	○	<a href="#">KR952321</a>	②	●	●	■
	●	<a href="#">KR952322</a>	②	●	●	■
<b>up in-line 80 wallwasher</b> ⌀ LxW 85x85 D 84	○	<a href="#">KR952371</a>	③	●	●	■
	●	<a href="#">KR952372</a>	③	●	●	■
<b>up in-line 80 circular</b> ⌀ Ø 85 D 84 Diffusing lens incl.	○	<a href="#">KR952801</a>	①	●	●	■
	●	<a href="#">KR952802</a>	①	●	●	■
<b>up in-line 80 circular</b> ⌀ Ø 85 D 84 15° optic & anti-glare louvre incl.	○	<a href="#">KR952821</a>	②	●	●	■
	●	<a href="#">KR952822</a>	②	●	●	■
<b>up in-line 80 circular wallwasher</b> ⌀ Ø 85 D 84	○	<a href="#">KR952871</a>	③	●	●	■
	●	<a href="#">KR952872</a>	③	●	●	■
<b>Optional accessories</b>						
Matchbox		<a href="#">KR752103</a>	Matchbox for up in-line 80			
		<a href="#">KR752603</a>	Matchbox for up in-line 80 circular			
Driver ①		<a href="#">KR772830</a>	LED driver, 700 mA, ON/OFF, 35W (IP68)			
		<a href="#">KR772752</a>	LED driver, 700 mA, 1-10V, 12W (IP67)			
		<a href="#">KR772753</a>	LED driver, 700 mA, DALI, 70W (IP68)			


	CRI	CCT	Wattage	Drive current	Fixture lumen
① LED	CRI80+	2700K	8,4W	700mA	272lm
	CRI90	2700K	8,4W	700mA	272lm
② LED	CRI80+	2700K	8,4W	700mA	458lm
	CRI90	2700K	8,4W	700mA	458lm
③ LED	CRI80+	2700K	8,4W	700mA	534lm
	CRI90	2700K	8,4W	700mA	534lm

## REMARKS


① Must be placed on remote

Thickness boardmaterial:  
6-35mm  
Gear excluded.  
◆ IP67 - IK10





Matchbox up in-line 80



Matchbox up in-line 80 circular



# kreon up in-line 165



**up in-line 165**  
 Ø LxW 156x156 D 97  
 Gear: excl., anti-glare louvre incl.

**up in-line 165 wallwasher**  
 Ø LxW 156x156 D 97  
 Gear: excl.

**up in-line 165 circular**  
 Ø Ø156 D 97  
 Gear: excl., anti-glare louvre incl.

**up in-line 165 circular wallwasher**  
 Ø Ø156 D 97  
 Gear: excl.

### Optional accessories

Matchbox

<b>KR782103</b>	Matchbox for up in-line 165
<b>KR782104</b>	Matchbox for gear for up in-line 165 (for fixtures gear excl.)
<b>KR782603</b>	Matchbox for up in-line 165 circular
<b>KR782604</b>	Matchbox for gear for up in-line 165 circular (for fixtures gear excl.)

Coupling sleeve

<b>KR782105</b>	Coupling sleeve
-----------------	-----------------


Driver

<b>KR772630</b>	LED driver, 700 mA, ON/OFF, 30W (IP68)
<b>KR772852</b>	LED driver, 700 mA, 1-10V, 30W (IP67)
<b>KR772853</b>	LED driver, 700 mA, DALI, 30W (IP68)


		CRI	CCT	Wattage	Drive current	Fixture lumen
①	LED	CR183	2700K	15,2W	700mA	824lm
		CR190	2700K	17,1W	700mA	824lm
②	LED	CR183	2700K	15,2W	700mA	1099lm
		CR190	2700K	17,1W	700mA	1099lm

**REMARKS**  
 Thickness boardmaterial:  
 6-35mm  
 IP67 - IK10


Matchbox up in-line 165




Matchbox up in-line 165 circular



Matchbox up in-line 165 for gear



Matchbox up in-line 165 for gear circular



Colour	KR-code	Light sources	9327 2700K, CR83	9027 2700K, CR90	C5 Maritime	Optional accessories
○	<b>KR982321</b>	①	●	●	●	■
●	<b>KR982322</b>	①	●	●	●	■
○	<b>KR982381</b>	②	●	●	●	■
●	<b>KR982382</b>	②	●	●	●	■
○	<b>KR982821</b>	①	●	●	●	■
●	<b>KR982822</b>	①	●	●	●	■
○	<b>KR982881</b>	②	●	●	●	■
●	<b>KR982882</b>	②	●	●	●	■