

PRACHT®

PRACHT®

TUBIS BL



Inc1. DV

Factory-made 3x1.5 mm²
through-wiring

NOBLE

Stainless
steel clamps

Aluminium

Aluminium carrier for
optimal thermal management

Fast

Solid PBT end caps,
extremely fast connection

Resistant

High-quality PMMA-blend
round tube (IK06, Ø70 mm)

Breathing

No condensation thanks
to climate membrane

CASING PMMA-Blend round tube.

END CAPS Solid PBT end caps.

SEALS Extremely short, age-resistant silicone seals.

ELECTRICAL COMPONENTS High power LED, LED converter.

ASSEMBLY Variable mounting distances by PRACHT-CLAMP-SYSTEM. Suitable for ceilings, wall, pendant and rail mounting.

FIELDS OF APPLICATION Washing plants, wet rooms, workshops, acid and alkaline cleaning plants and oily environments.

Individual luminaire, color temperature 4000 K, Ra>80, diameter 70mm

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x24 W	135° wide	2800 lm	5240004	1310 mm	1.8 kg
1x45 W	135° wide	5400 lm	5240014	1310 mm	1.8 kg
1x32 W	135° wide	3800 lm	5240005	1610 mm	2.2 kg
1x54 W	135° wide	6500 lm	5240015	1610 mm	2.2 kg

WATER SPORTSMAN

**TIGHT ACID-ALKALI-RESISTANT
TUBULAR LUMINAIRE
STURDY FAST ASSEMBLY ENEC
FOR UNPROTECTED OUTDOOR AREA
MODERN DESIGN**

3

YEAR
WARRANTY



50.000 h
OPERATIONAL LIFETIME



A++

**IP67
IP69K**



INCL. DV
(3x1.5mm²)



-20°C ... +40°C

Protection class I according to EN 60598
Protection type IP67/IP69K
AC/DC 220-240 V 50/60 Hz *registered

PRACHT.COM

+49 64 66 / 91 40-0