

Project: Medical Office Celle Germany, Germany




Diversity Design with Adjustable Spot Light



NEKO / FUSION / FS1
Adjustable Spotlight

NEKO / FUSION / FS2
Adjustable Spotlight





LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code						
2 W	3 W	3 V	700 mA	80	2700K	15°	220lm	160lm	FS1-8271502N-WN						
						30°	220lm	160lm	FS1-8273002N-WN						
						3000K	15°	250lm	170lm	FS1-8301502N-WN					
							30°	250lm	170lm	FS1-8303002N-WN					
						4000K	15°	280lm	180lm	FS1-8401502N-WN					
							30°	280lm	180lm	FS1-8403002N-WN					
						2 W	3 W	3 V	700 mA	80	2700K	15°	220lm	160lm	FS1-8271502N-BN
												30°	220lm	160lm	FS1-8273002N-BN
3000K	15°	250lm	170lm	FS1-8301502N-BN											
	30°	250lm	170lm	FS1-8303002N-BN											
4000K	15°	280lm	180lm	FS1-8401502N-BN											
	30°	280lm	180lm	FS1-8403002N-BN											

Code Remark: N=(NO Driver) F=(ON-OFF) A=(1-10V Dim) D=(DALI Dim)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code						
4 W	6 W	6 V	700 mA	80	2700K	15°	450lm	330lm	FS2-8271504N-WN						
						30°	450lm	330lm	FS2-8273004N-WN						
						3000K	15°	500lm	350lm	FS2-8301504N-WN					
							30°	500lm	350lm	FS2-8303004N-WN					
						4000K	15°	550lm	400lm	FS2-8401504N-WN					
							30°	550lm	400lm	FS2-8403004N-WN					
						4 W	6 W	6 V	700 mA	80	2700K	15°	450lm	330lm	FS2-8271504N-BN
												30°	450lm	330lm	FS2-8273004N-BN
3000K	15°	500lm	350lm	FS2-8301504N-BN											
	30°	500lm	350lm	FS2-8303004N-BN											
4000K	15°	550lm	400lm	FS2-8401504N-BN											
	30°	550lm	400lm	FS2-8403004N-BN											

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
7 W	9 W	9 V	700 mA	80	2700K	15°	700lm	500lm	FS3-8271507N-WN	
						30°	700lm	500lm	FS3-8273007N-WN	
						3000K	15°	750lm	550lm	FS3-8301507N-WN
							30°	750lm	550lm	FS3-8303007N-WN
						4000K	15°	800lm	600lm	FS3-8401507N-WN
							30°	800lm	600lm	FS3-8403007N-WN



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
7 W	9 W	9 V	700 mA	80	2700K	15°	700lm	500lm	FS3-8271507N-BN	
						30°	700lm	500lm	FS3-8273007N-BN	
						3000K	15°	750lm	550lm	FS3-8301507N-BN
							30°	750lm	550lm	FS3-8303007N-BN
						4000K	15°	800lm	600lm	FS3-8401507N-BN
							30°	800lm	600lm	FS3-8402507N-BN

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Trimless available



Trimless code for FS3-8301507N-WN
FST3-8301507N-WN



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
13 W	15 W	18 V	700 mA	80	2700K	15°	1400lm	1000lm	FS6-8271513N-WN	
						30°	1400lm	1000lm	FS6-8273013N-WN	
						3000K	15°	1500lm	1050lm	FS6-8301513N-WN
							30°	1500lm	1050lm	FS6-8303013N-WN
						4000K	15°	1600lm	1100lm	FS6-8401513N-WN
							30°	1600lm	1100lm	FS6-8403013N-WN



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
13 W	15 W	18 V	700 mA	80	2700K	15°	1400lm	1000lm	FS6-8271513N-BN	
						30°	1400lm	1000lm	FS6-8273013N-BN	
						3000K	15°	1500lm	1050lm	FS6-8301513N-BN
							30°	1500lm	1050lm	FS6-8303013N-BN
						4000K	15°	1600lm	1100lm	FS6-8401513N-BN
							30°	1600lm	1100lm	FS6-8403013N-BN

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Trimless available



Trimless code for FS6-8301513N-WN
FST6-8301513N-WN



NEKO / FUSION / FF3-FS1
Adjustable Spotlight



NEKO / FUSION / FF6-FS2
Adjustable Spotlight



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
9 W	11 W	12 V	700 mA	80	2700K	24°	900lm	650lm	FFS1-8272409N-WB	
						40°	900lm	650lm	FFS1-8274009N-WB	
						3000K	24°	1000lm	700lm	FFS1-8302409N-WB
							40°	1000lm	700lm	FFS1-8304009N-WB
						4000K	24°	1100lm	800lm	FFS1-8402409N-WB
							40°	1100lm	800lm	FFS1-8404009N-WB



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
9 W	11 W	12 V	700 mA	80	2700K	24°	900lm	650lm	FFS1-8272409N-BB	
						40°	900lm	650lm	FFS1-8274009N-BB	
						3000K	24°	1000lm	700lm	FFS1-8302409N-BB
							40°	1000lm	700lm	FFS1-8304009N-BB
						4000K	24°	1100lm	800lm	FFS1-8402409N-BB
							40°	1100lm	800lm	FFS1-8404009N-BB

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Trimless available



Trimless code for FFS1-8304009N-WN
FFS3-8304009N-WN



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
17 W	19 W	24 V	700 mA	80	2700K	24°	1900lm	1300lm	FFS2-8272417N-WB	
						40°	1900lm	1300lm	FFS2-8274017N-WB	
						3000K	24°	2000lm	1400lm	FFS2-8302417N-WB
							40°	2000lm	1400lm	FFS2-8304017N-WB
						4000K	24°	2200lm	1500lm	FFS2-8402417N-WB
							40°	2200lm	1500lm	FFS2-8404017N-WB



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
17 W	19 W	24 V	700 mA	80	2700K	24°	1900lm	1300lm	FFS2-8272417N-BB	
						40°	1900lm	1300lm	FFS2-8274017N-BB	
						3000K	24°	2000lm	1400lm	FFS2-8302417N-BB
							40°	2000lm	1400lm	FFS2-8304017N-BB
						4000K	24°	2200lm	1500lm	FFS2-8402417N-BB
							40°	2200lm	1500lm	FFS2-8404017N-BB

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Trimless available



Trimless code for FFS2-8304017N-WN
FFS4-8304017N-WN

