



DESCRIPTION: TREK / TAIGA

- Lighting head and module in die-cast aluminium
- Aluminium profile 200 x 100mm tube
- Polycarbonate bowl
- Polyester powder coating, any colour available
- IP66 Module
- IK10
- Class I or II
- Weight: 23 kg
- Standard BLS LED strips equipped with **QUADRALENS** lenses
- Colour temperatures: 2400 K, 2700 K, 3000 K and 4000 K

CITIZEN REFERENCE POINTS: TREK / TAIGA

- Materials used: Steel 56%, Aluminium 39%, Plastic 2%, Other 3%
- Complies with the RoHS directive
- High recyclability rate

INSTALLATION: TREK / TAIGA

- Cast iron base
- Internal fixing using 4 anchor rods, Ø 12 mm

MAINTENANCE: TREK / TAIGA

- Removable lighting head
- Access to the equipment after removal of the profiled tube

TREK / TAIGA	
Rearward light spill cover⁽¹⁾ (factory or site assembly)	○
DALI (construction)	○
Dimming 5 (preset)	○
FC	Compatible with standard version, Dimming 5 or DALI option
Motion DALI (set in the bottom of the pole)	○
POLEDRIVE (set in the bottom of the pole)	○

(1) Rearward light spill cover optional except for EPD, EPG, ECa

Glossary:

● Standard ○ Option - Not available

EAH: Dedicated LED module for accessibility of disabled persons (PMR), **POLEDRIVE:** preset at the bottom of the pole / night dimming calculator with 2 configurable thresholds, set in the bottom of the pole, **Dimming 5:** night dimming calculator with 5 configurable thresholds, **Motion DALI:** Detector integrated to the luminaire, adjustable at pole base, **DALI:** compatible with the DALI protocol, **FC:** Compensated flux

PHOTOMETRIC DISTRIBUTIONS: TREK / TAIGA

