


**NEKO / GAME350**  
Ceiling Light System



12W CRI180 2700K
16W CRI190 3000K 4000K
Tunable White Available
OSRAM 50,000h@L80B10
UGR < 19
IP40
5 YEAR WARRANTY
CB
CE
ENERGY STAR



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
12 W	14 W	34 V	350 mA	80	2700K	90°	1800lm	1300lm	GASM-8279012N-BN
						3000K 90°	1900lm	1400lm	GASM-8309012N-BN
						4000K 90°	2000lm	1500lm	GASM-8409012N-BN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GASM-8279016N-BN
						3000K 90°	2600lm	2000lm	GASM-8309016N-BN
						4000K 90°	2800lm	2200lm	GASM-8409016N-BN
12 W	14 W	34 V	350 mA	80	2700K	90°	1800lm	1300lm	GASM-8279012N-WN
						3000K 90°	1900lm	1400lm	GASM-8309012N-WN
						4000K 90°	2000lm	1500lm	GASM-8409012N-WN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GASM-8279016N-WN
						3000K 90°	2600lm	2000lm	GASM-8309016N-WN
						4000K 90°	2800lm	2200lm	GASM-8409016N-WN



Black



White

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)



Black



White



Black



White

Optional accessory



Magneto Uplight Module 800

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
12 W	14 W	34 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPW-8279012N-BN
						3000K 90°	1900lm	1400lm	GAPW-8309012N-BN
						4000K 90°	2000lm	1500lm	GAPW-8409012N-BN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPW-8279016N-BN
						3000K 90°	2600lm	2000lm	GAPW-8309016N-BN
						4000K 90°	2800lm	2200lm	GAPW-8409016N-BN

Standard pendant length: 1200mm

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
12 W	14 W	34 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPW-8279012N-WN
						3000K 90°	1900lm	1400lm	GAPW-8309012N-WN
						4000K 90°	2000lm	1500lm	GAPW-8409012N-WN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPW-8279016N-WN
						3000K 90°	2600lm	2000lm	GAPW-8309016N-WN
						4000K 90°	2800lm	2200lm	GAPW-8409016N-WN

Standard pendant length: 1200mm

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
12 W	14 W	34 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPR-8279012N-BN
						3000K 90°	1900lm	1400lm	GAPR-8309012N-BN
						4000K 90°	2000lm	1500lm	GAPR-8409012N-BN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPR-8279016N-BN
						3000K 90°	2600lm	2000lm	GAPR-8309016N-BN
						4000K 90°	2800lm	2200lm	GAPR-8409016N-BN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
12 W	14 W	34 V	350 mA	80	2700K	90°	1800lm	1300lm	GAPR-8279012N-WN
						3000K 90°	1900lm	1400lm	GAPR-8309012N-WN
						4000K 90°	2000lm	1500lm	GAPR-8409012N-WN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GAPR-8279016N-WN
						3000K 90°	2600lm	2000lm	GAPR-8309016N-WN
						4000K 90°	2800lm	2200lm	GAPR-8409016N-WN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
8 W	10 W	33 V	250 mA	80	2700K	110°	900lm	800lm	UM35-827A108N-NN
						3000K 110°	950lm	850lm	UM35-830A108N-NN
						4000K 110°	1050lm	950lm	UM35-840A108N-NN


Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Code for GAPR-8309012N-WN with Uplight Module  
GAPR-8309012N-WN-U

**NEKO / GAME450**  
Ceiling Light System



16W CRI80 2700K Tunable White Available 90° OSRAM 60,000h@L80B10 UGR < 19 IP40 5 YEAR WARRANTY CB CE ENEC



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GBSM-8279016N-BN	
							3000K 90°	2600lm	2000lm	GBSM-8309016N-BN
							4000K 90°	2800lm	2200lm	GBSM-8409016N-BN
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GBSM-8279024N-BN	
							3000K 90°	3700lm	2800lm	GBSM-8309024N-BN
							4000K 90°	4000lm	3000lm	GBSM-8409024N-BN
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GBSM-8279016N-WN	
							3000K 90°	2600lm	2000lm	GBSM-8309016N-WN
							4000K 90°	2800lm	2200lm	GBSM-8409016N-WN
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GBSM-8279024N-WN	
							3000K 90°	3700lm	2800lm	GBSM-8309024N-WN
							4000K 90°	4000lm	3000lm	GBSM-8409024N-WN



Black




White

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)



Black



White



Black



White

Optional accessory



Magnetic Uplight Module 450

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPW-8279016N-BN	
							3000K 90°	2600lm	2000lm	GBPW-8309016N-BN
							4000K 90°	2800lm	2200lm	GBPW-8409016N-BN
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPW-8279024N-BN	
							3000K 90°	3700lm	2800lm	GBPW-8309024N-BN
							4000K 90°	4000lm	3000lm	GBPW-8409024N-BN

Standard pendant length: 1200mm

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPW-8279016N-WN	
							3000K 90°	2600lm	2000lm	GBPW-8309016N-WN
							4000K 90°	2800lm	2200lm	GBPW-8409016N-WN
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPW-8279024N-WN	
							3000K 90°	3700lm	2800lm	GBPW-8309024N-WN
							4000K 90°	4000lm	3000lm	GBPW-8409024N-WN

Standard pendant length: 1200mm

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPR-8279016N-BN	
							3000K 90°	2600lm	2000lm	GBPR-8309016N-BN
							4000K 90°	2800lm	2200lm	GBPR-8409016N-BN
24 W	26 W	36 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPR-8279024N-BN	
							3000K 90°	3700lm	2800lm	GBPR-8309024N-BN
							4000K 90°	4000lm	3000lm	GBPR-8409024N-BN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
16 W	18 W	34 V	500 mA	80	2700K	90°	2400lm	1900lm	GBPR-8279016N-WN	
							3000K 90°	2600lm	2000lm	GBPR-8309016N-WN
							4000K 90°	2800lm	2200lm	GBPR-8409016N-WN
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GBPR-8279024N-WN	
							3000K 90°	3700lm	2800lm	GBPR-8309024N-WN
							4000K 90°	4000lm	3000lm	GBPR-8409024N-WN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code	
11 W	13 W	33 V	350 mA	80	2700K	110°	1100lm	1000lm	UM45-827A111N-WN	
							3000K 110°	1200lm	1100lm	UM45-830A111N-WN
							4000K 110°	1300lm	1200lm	UM45-840A111N-WN

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Code for GBPR-8309016N-WN with Uplight Module  
GBPR-8309016N-WN-U

**NEKO / GAME600**  
Ceiling Light System



**24W** **CRI180** **2700K** **Tunable White**  
**36W** **CRI190** **3000K** **Available**  
**46W** **4000K**


**OSRAM**  
 50,000h@L80B10

**UGR < 19**

**IP40**

**5 YEAR WARRANTY**

**CB CE**



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GCSM-8279024N-BN
							3700lm	2800lm	GCSM-8309024N-BN
							4000lm	3000lm	GCSM-8409024N-BN
36 W	40 W	34 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCSM-8279036N-BN
							6200lm	4700lm	GCSM-8309036N-BN
							6600lm	4900lm	GCSM-8409036N-BN
46 W	50 W	34 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCSM-8279046N-BN
							8100lm	6100lm	GCSM-8309046N-BN
							8600lm	6400lm	GCSM-8409046N-BN



Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)



Black



White



Black



White

Optional accessory



Magnetic Uplight Module 800

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GCPW-8279024N-BN
							3700lm	2800lm	GCPW-8309024N-BN
							4000lm	3000lm	GCPW-8409024N-BN
36 W	40 W	34 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCPW-8279036N-BN
							6200lm	4700lm	GCPW-8309036N-BN
							6600lm	4900lm	GCPW-8409036N-BN
46 W	50 W	34 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCPW-8279046N-BN
							8100lm	6100lm	GCPW-8309046N-BN
							8600lm	6400lm	GCPW-8409046N-BN

Standard pendant length: 1200mm

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	GCPW-8279024N-WN
							3700lm	2800lm	GCPW-8309024N-WN
							4000lm	3000lm	GCPW-8409024N-WN
36 W	40 W	34 V	1050 mA	80	2700K	90°	5800lm	4400lm	GCPW-8279036N-WN
							6200lm	4700lm	GCPW-8309036N-WN
							6600lm	4900lm	GCPW-8409036N-WN
46 W	50 W	34 V	1400 mA	80	2700K	90°	7200lm	5800lm	GCPW-8279046N-WN
							8100lm	6100lm	GCPW-8309046N-WN
							8600lm	6400lm	GCPW-8409046N-WN

Standard pendant length: 1200mm

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	G CPR-8279024N-BN
							3700lm	2800lm	G CPR-8309024N-BN
							4000lm	3000lm	G CPR-8409024N-BN
36 W	40 W	34 V	1050 mA	80	2700K	90°	5800lm	4400lm	G CPR-8279036N-BN
							6200lm	4700lm	G CPR-8309036N-BN
							6600lm	4900lm	G CPR-8409036N-BN
46 W	50 W	34 V	1400 mA	80	2700K	90°	7200lm	5800lm	G CPR-8279046N-BN
							8100lm	6100lm	G CPR-8309046N-BN
							8600lm	6400lm	G CPR-8409046N-BN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
24 W	26 W	34 V	700 mA	80	2700K	90°	3500lm	2600lm	G CPR-8279024N-WN
							3700lm	2800lm	G CPR-8309024N-WN
							4000lm	3000lm	G CPR-8409024N-WN
36 W	40 W	34 V	1050 mA	80	2700K	90°	5800lm	4400lm	G CPR-8279036N-WN
							6200lm	4700lm	G CPR-8309036N-WN
							6600lm	4900lm	G CPR-8409036N-WN
46 W	50 W	34 V	1400 mA	80	2700K	90°	7200lm	5800lm	G CPR-8279046N-WN
							8100lm	6100lm	G CPR-8309046N-WN
							8600lm	6400lm	G CPR-8409046N-WN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional


Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
18 W	20 W	36 V	500 mA	80	2700K	110°	1800lm	1600lm	UM60-827A118N-NN
							1900lm	1700lm	UM60-830A118N-NN
							2000lm	1800lm	UM60-840A118N-NN

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Code for G CPR-8309036N-WN with Uplight Module  
G CPR-8309036N-WN-U

**NEKO / GAME900**  
Ceiling Light System



LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDSM-8279065N-BN
					3000K	90°	10500lm	8000lm	GDSM-8309065N-BN
					4000K	90°	11000lm	8400lm	GDSM-8409065N-BN

Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDSM-8279065N-WN
					3000K	90°	10500lm	8000lm	GDSM-8309065N-WN
					4000K	90°	11000lm	8400lm	GDSM-8409065N-WN

White

Code Remark: N=(NO Driver) F=(ON-OFF) A=(1-10V Dim) D=(DALI Dim)

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPW-8279065N-BN
					3000K	90°	10500lm	8000lm	GDPW-8309065N-BN
					4000K	90°	11000lm	8400lm	GDPW-8409065N-BN

Standard pendant length: 1200mm



Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPW-8279065N-WN
					3000K	90°	10500lm	8000lm	GDPW-8309065N-WN
					4000K	90°	11000lm	8400lm	GDPW-8409065N-WN

Standard pendant length: 1200mm



White

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPR-8279065N-BN
					3000K	90°	10500lm	8000lm	GDPR-8309065N-BN
					4000K	90°	11000lm	8400lm	GDPR-8409065N-BN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional



Black

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
65 W	68 W	46 V	1400 mA	80	2700K	90°	9900lm	7600lm	GDPR-8279065N-WN
					3000K	90°	10500lm	8000lm	GDPR-8309065N-WN
					4000K	90°	11000lm	8400lm	GDPR-8409065N-WN

Standard pendant length: 1000mm (customized lengths available)

Remark: Field cuttable pendant rod solution optional



White

Code Remark: N=(NO Driver) F=(ON-OFF) A=(1-10V Dim) D=(DALI Dim)

Optional accessory



Magnate Uplight Module 000

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	LED Output	System Output	Code
25 W	28 W	36 V	700 mA	80	2700K	110°	2500lm	2200lm	UM90-827A125N-NN
					3000K	110°	2700lm	2400lm	UM90-830A125N-NN
					4000K	110°	2900lm	2600lm	UM90-840A125N-NN

Code Remark: N=(NO Driver) F=(ON-OFF) P=(Phase Dim) A=(1-10V Dim) D=(DALI Dim)

Code for GDPR-8309065N-WN with Uplight Module  
GDPR-8309065N-WN-U